



## RF3334 Series Key Fobs



- ▶ Uniquely coded arm and disarm buttons
- ▶ Panic alarm
- ▶ LED indicator
- ▶ Programmable option buttons

The RF3334 Series Key Fobs includes the RF3334 and the RF3334E. The RF3334 transmits at a frequency of 304.00 MHz while the RF3334E transmits at 433.42 MHz. Both models are wireless and have four buttons. Each model allows you to arm and disarm the security system or send a panic alarm. Programmed with a unique code, each model works exclusively with your compatible security system. Two option buttons are user-defined to perform additional functions.

### Functions

#### Panic Alarm

The RF3334 Series can send a panic code to your monitoring company if your security system is programmed to do so. Press both the lock and unlock buttons simultaneously for two seconds to send a panic alarm.

#### LED Indicator

The LED flashes to indicate a signal was sent to your security system.

#### Programmable Option Buttons

The RF3334 Series can be programmed to control additional devices in your protected area. Two option buttons are available. Possible programming choices include turning on lights or opening the garage door.

### Certifications and Approvals

#### RF3334

Listings and Approvals: Industry Canada  
 Complies with: FCC (ESV-0407-2)

#### RF3334E

Listings and Approvals: **CE**

### Installation/Configuration Notes

#### Compatibility Information

Model	Receivers	Control Panels
RF3334	RF3212	Solution Ultima 844, 862, and 880, CC488
	RF3213	VR-8
	RF3222	DS7400XiV4
	RF3224	DS7240, DS7220, D6412, and D4412
RF3334E	RF3212E	Solution Ultima 844, 862, and 880, CC488
	RF3213E	VR-8
	RF3222E	DS7400XiV4
	RF3227E	DS7240, DS7220, D6412, and D4412
	RF3228E	Marise
RF3249E	DA (Abacus)	

## Recommended Batteries

The following battery types are recommended for correct operation of your key fob: Duracell® DL2025, Eveready® CR2025, or Panasonic® CR2025.

## Technical Specifications

### Environmental Considerations

Relative Humidity:	0% to 95% (non-condensing)
Temperature (operating):	-29°C to +65°C (-20°F to +150°F) <i>For UL listed requirements, the temperature range is 0°C to +49°C (+32°F to +120°F)</i>

### Mechanical Properties

Dimensions:	3.8 cm x 6.3 cm x 1.3 cm (1.5 in. x 2.5 in. x 0.5 in.)
-------------	--

### Power Requirements

Batteries:	Two 3 VDC lithium batteries
Battery Life:	5 to 6 years under normal operating conditions with recommended battery types

### Transmission Characteristics

#### Frequency

RF3334:	304.00 MHz
RF3334E:	433.42 MHz

### Trademarks

Duracell® is a registered trademark of the Gillette Company, USA, in the United States and/or other countries.

Eveready® is a registered trademark of Eveready Battery Company, Inc.

Panasonic® is a registered trademark of Matsushita Electric Industrial Co., Ltd.

## Ordering Information

RF3334 Four-Button Wireless Key Fob (304 MHz)	RF3334
RF3334E Four-Button Wireless Key Fob (433.42 MHz)	RF3334E

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Americas:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Asia-Pacific:**  
Bosch Security Systems Pte Ltd  
38C Jalan Pemimpin  
Singapore 577180  
Phone: +65 6319 3450  
Fax: +65 6319 3499  
apr.securitysystems@bosch.com  
www.boschsecurity.com

**Represented by**